



PLASTIC SPIRAL WRAP PROTECTOR



DME & JDE GROUP
YOUR CONNECTORS & HOSES OEM SOLUTIONS

Protection From Abrasion, Shocks & Rubbing

DME&JDE

Protection From Abrasion, Shocks & Rubbing

Texture

The material is PP (polypropylene), with all raw materials produced by Sinopec.

Features

- Wear-resistant
- Aesthetically pleasing
- Flame-retardant
- Oil-resistant
- Anti-freeze
- Aging-resistant
- Corrosion-resistant
- High and low temperature-resistant (-40°C to 80°C)



Application & Benefits

This spiral wrap protector is designed to safeguard hose assembly parts during operation. It effectively reduces the impact of various internal and external operating conditions on rubber hoses, including:

- Preventing rubber hose whipping under high pressure
- Mitigating hose abrasion in construction sites, mines, and quarries
- Protecting against hose corrosion caused by seawater during marine operations

By limiting the hose's movement range, this product helps extend the service life of your hydraulic hoses.

Web: <https://www.dmejde.com>
 E-mail: info@dmejde.com



DME&JDE

Protection Against Abrasion, Shocks & Rubbing



Material & Features & Benefits

- Polypropylene (PP).
- Exceptional anti-crushing performance. [AS 1145: Test passed].
- High abrasion resistance. [ISO 6954: Test passed].
- Long life & good resistance to UV rays. [ISO 4892-2: Test passed]
- Flame retardant. [ISO 1210: Test passed]
- Easy to fit.



Specifications for Flat Surface Plastic Spiral Wrap Protector

Type (mm)	I.D. (mm)	O.D. (mm)	W. (mm)	P. (mm)	Recommended Hose Range (mm)	Length (m/roll)
D&J-HDPE-1-8	8.0	10.0	1.0	12.0	8-12	2/20/50/100/200
D&J-HDPE-1-10	10.0	12.0	1.0	12.0	10-14	2/20/50/100/200
D&J-HDPE-1-12	12.0	14.0	1.0	12.0	12-16	2/20/50/100/200
D&J-HDPE-1-14	14.0	16.0	1.0	13.0	14-18	2/20/50/100/200
D&J-HDPE-1-16	16.0	18.8	1.4	14.5	16-20	2/20/50/100/200
D&J-HDPE-1-18	18.0	21.2	1.6	15.5	18-22	2/20/50/100
D&J-HDPE-1-19	19.0	22.2	1.6	15.5	19-22	2/20/50/100
D&J-HDPE-1-21	21.0	24.6	1.8	18.5	21-25	2/20/50/100
D&J-HDPE-1-22	22.0	25.6	1.8	18.5	22-25	2/20/50/100
D&J-HDPE-1-25	25.0	28.6	1.8	21.5	25-30	2/20/50/100/150
D&J-HDPE-1-26	26.0	29.6	1.8	21.5	26-30	2/20/50/100/150
D&J-HDPE-1-28	28.0	31.8	1.9	22.5	28-32	2/20/50/100/150
D&J-HDPE-1-30	30.0	34.0	2.0	23.0	30-35	2/20/50/100
D&J-HDPE-1-32	32.0	36.0	2.0	23.0	32-38	2/20/50/100
D&J-HDPE-1-35	35.0	39.0	2.0	24.0	35-40	2/20/50/100
D&J-HDPE-1-38	38.0	42.0	2.0	24.0	38-43	2/20/50/100
D&J-HDPE-1-40	40.0	45.6	2.8	25.0	40-45	2/20/50
D&J-HDPE-1-42	42.0	48.0	3.0	26.0	42-48	2/20/50
D&J-HDPE-1-45	45.0	51.0	3.0	27.0	45-50	2/20/50
D&J-HDPE-1-48	48.0	54.0	3.0	27.0	48-52	2/20/50
D&J-HDPE-1-50	50.0	56.0	3.0	27.0	50-55	2/20/50
D&J-HDPE-1-51	51.0	57.0	3.0	27.0	51-56	2/20/50
D&J-HDPE-1-60	60.0	66.0	3.0	26.5	60-65	2/20/50
D&J-HDPE-1-63	63.0	69.0	3.0	27.0	63-70	2/20/50
D&J-HDPE-1-68	68.0	74.0	3.0	30.0	68-72	2/20/50
D&J-HDPE-1-74	74.0	84.4	5.2	47.5	74-80	2/10/20
D&J-HDPE-1-80	80.0	89.0	4.5	40.5	80-85	2/10
D&J-HDPE-1-88	88.0	98.0	5.0	43.0	88-95	2/10
D&J-HDPE-1-100	100.0	110.0	5.0	45.0	100-110	2/10

Web: <https://www.dmejde.com>
E-mail: info@dmejde.com

